Computing with Pathway/Genome Databases

Markus Krummenacker
Bioinformatics Research Group
SRI International
kr@ai.sri.com

BioCyc.org
EcoCyc.org
MetaCyc.org
HumanCyc.org



Data Exchange

- Java API and Perl API : read & modify
- BioPAX Export: since Pathway Tools 9.0
 - Biopax.org
- Export of entire PGDB as Flatfiles
- Export of Reactions as SBML -- sbml.org
- Import/Export of Pathways: between PGDBs
- Import/Export of Selected Frames, for Spreadsheets
- Import/Export of Compounds as Molfile, CML
- Registering/Publishing PGDBs on WWW
- BioWarehouse: Loader for Flatfiles, SQL access
 - http://bioinformatics.ai.sri.com/biowarehouse/



Programmatic Access to BioCyc

Common LISP

- Native language of Pathway Tools
- Interactive & Mature Environment
- Full Access to the Data & Many Utility Functions
- Source code is available for academics

PerICyc

- API of Functions, Exposed to Perl
- Communication through UNIX Socket

JavaCyc

- API of Functions, Exposed to Java
- Communication through UNIX Socket



BioCyc Schema Basics

- Object-Oriented, Class & Instance Frames
- Frame Representation System, named Ocelot
- Query API: GFP (Generic Frame Protocol)
- one KB per PGDB, persistently stored as:
 - Preloaded into Runtimes
 - Ocelot file: single-user
 - RDBMS: MySQL-4 or Oracle-10 : multi-user, change-logging
- Frames have named Slots
- Slots
 - Single or Multiple Values
 - Numbers, Strings, or Pointers to other Frames (pot. w/ Inverse)
 - Slot Units define the Properties of a Slot
- Annotations on Slot Values
 - used for Stoichiometry Coefficients, Compartments, Citations, etc.



Principal Classes 1

- Class names are capitalized, plural, separated by dashes
- Genetic-Elements, with subclasses:
 - Chromosomes
 - Plasmids
- Genes
- Transcription-Units
- RNAs
 - rRNAs, snRNAs, tRNAs, Charged-tRNAs
- Proteins, with subclasses:
 - Polypeptides
 - Protein-Complexes




Principal Classes 2

- Reactions, with subclasses:
 - Transport-Reactions
- Enzymatic-Reactions
- Pathways
- Compounds-And-Elements



Slot Links



Example of a Single GFP Call

• The General Pattern:

```
(gfp-call frame-ID slot-ID value ...)
```

LISP

```
(get-slot-values 'TRYPSYN-RXN 'LEFT)
==> (INDOLE-3-GLYCEROL-P SER)
```

Perl

```
my $cyc = perlcyc -> new("ECOLI");
my @cpds = $cyc -> get_slot_all_values("Trypsyn-Rxn", "Left");
```



More Information

Pathway Tools WWW Site, Tutorial Slides

- http://bioinformatics.ai.sri.com/ptools/
- http://bioinformatics.ai.sri.com/ptools/3schema.ppt
- http://bioinformatics.ai.sri.com/ptools/6lisp.ppt
- http://bioinformatics.ai.sri.com/ptools/examples.lisp

PerlCyc & JavaCyc API, includes some relationships

- http://www.arabidopsis.org/tools/aracyc/perlcyc/
- http://www.arabidopsis.org/tools/aracyc/javacyc/
- nav/10.0/lisp/relationships.lisp
- Pathway Tools User's Guide, Volume I
 - Appendix A: Guide to the Pathway Tools Schema
- Curator's Guide: Compound Classes, Polymerization
 - http://bioinformatics.ai.sri.com/ptools/curatorsguide.pdf



Simple Query Example

Perl

```
use perlcyc;
my $cyc = perlcyc -> new("ECOLI");
my @enzrxns = $cyc -> get_class_all_instances("|Enzymatic-Reactions|");
## We check every instance of the class
foreach my $er (@enzrxns) {
  ## We test for whether the INHIBITORS-ALL
  ## slot contains the compound frame ATP
  my $bool = $cyc -> member_slot_value_p($er, "Inhibitors-All", "Atp");
  if ($bool) {
    ## Whenever the test is positive, we collect the value of the slot ENZYME.
    ## The results are printed in the terminal.
    my $enz = $cyc -> get_slot_value($er, "Enzyme");
    print STDOUT "$enz\n";
```

Simple Query Example

LISP

```
(defun atp-inhibits ()
  ;; We check every instance of the class
  (loop for x in (get-class-all-instances '|Enzymatic-Reactions|)
    :: We test for whether the INHIBITORS-ALL
    ;; slot contains the compound frame ATP
    when (member-slot-value-p x 'INHIBITORS-ALL 'ATP)
    ;; Whenever the test is positive, we collect the value of the slot ENZYME.
    ;; The collected values are returned as a list, once the loop terminates.
    collect (get-slot-value x 'ENZYME) )
;;; invoking the query:
(select-organism :org-id 'ECOLI)
(atp-inhibits)
(get-slot-values 'TRYPSYN-RXN 'LEFT)
==> (INDOLE-3-GLYCEROL-P SER)
```

Chokepoint Example

- For Antibiotic Target Development
- Find Strategic Essential Weak Links in Metabolism
- Many Compounds have just 1 Producing and consuming reaction

```
(defun chokepoint-1 ()
 (remove-duplicates
 (loop for cpd in (remove-if-not #'coercible-to-frame-p (all-substrates (all-rxns)))
    when (= 1 (length (get-slot-values cpd 'APPEARS-IN-LEFT-SIDE-OF))
             (length (get-slot-values cpd 'APPEARS-IN-RIGHT-SIDE-OF)))
    collect (get-slot-value cpd 'APPEARS-IN-LEFT-SIDE-OF)
   and
   collect (get-slot-value cpd 'APPEARS-IN-RIGHT-SIDE-OF)
 :test #'fequal)
;;; invoking the query:
(length (chokepoint-1)) ==> 348
```

Substring Search Example

 Find all that genes that contain a given substring within their common name or synonym list.



Getting started with Lisp

- pathway-tools –lisp
- (load "file") (compile-file "file.lisp")
- Emacs is a useful editor
- Pathway Tools source code is available: ask
- Lisp resources:

http://bioinformatics.ai.sri.com/ptools/ptools-resources.html



Some Gotchas

- Schema needs to be known in good detail
- Wall chart of schema and relations ?
- :test #'fequal
- Cascade of slot-values: check for NIL



Acknowledgements

SRI

 Peter Karp, Suzanne Paley, Pallavi Kaipa, Mario Latendresse, Ingrid Keseler, Ron Caspi, Michelle Green, Carol Fulcher

EcoCyc Project

J. Collado-Vides, J. Ingraham,
 I. Paulsen, M. Saier

MetaCyc Project

 Sue Rhee, Lukas Mueller, Peifen Zhang, Hartmut Foerster

•Funding sources:

- NIH National Center for Research Resources
- NIH National Institute of General Medical Sciences
- NIH National Human Genome Research Institute
- Department of Energy Microbial Cell Project
- DARPA BioSpice, UPC

